




High Power Type

# 51.6kWh Battery Rack



- › Highly advanced lithium-ion battery solution for mission-critical applications
- › Exceptionally high power performance (Up to 9 C-rate)
- › Exceedingly small footprint due to high energy density
- › 2-pole and 3-pole topology available
- › Long cycle and calendar life (Over 8,000 cycles and up to 15 years<sup>1</sup>)
- › Highly intelligent BMS<sup>2</sup> for sophisticated system control and monitoring

1. Depending on the load profile, the warranty condition may differ / 2. BMS: Battery Management System  
\*The image above is a reference, and the actual product may differ from the above image

# Battery Rack Specification

**Model: KST051607A15ADC00** (Previous Model Name: KUPS-1C5R-165S-HP-51-P04-F06)

Item	Specification	Remarks		
<b>Electrical</b>				
Configuration	Rack	5 modules in series		
	Module	1P33S		
	Cell	High Power		
Installed Energy	51.6kWh	-		
Usable Energy <sup>1</sup>	47.4kWh	@ 1P discharge, BOL		
Nominal Voltage	607.2Vdc	-		
Operating Voltage Range	528.0 ~ 681.4Vdc	-		
Float Voltage	674.8Vdc	-		
Charging	Power	Rated	51.6kW	1P
		Max <sup>2</sup>	103.2kW	2P
	Current	Rated	85.0A	1C
		Max <sup>2</sup>	170.0A	2C
Discharging	Power	Rated	51.6kW	1P
		Max <sup>2</sup>	303.6kW	5.8P, ≤7 min.
		Peak	361.2kW	7P, ≤5 min 30 sec.
			412.8kW	8P, ≤4 min 20 sec.
	Current	Rated	464.5kW	9P, ≤1 min.
			85.0A	1C
		Max <sup>2</sup>	500.0A	5.8C, ≤7 min.
			595.0A	7C, ≤5 min 30 sec.
Peak	680.0A	8C, ≤4 min 20 sec.		
	765.0A	9C, ≤1 min.		
Round Trip DC Efficiency	>95%	@ 1P, BOL		
Control Power	DC 24V	-		
<b>Mechanical</b>				
Dimension	580 (W) x 740 (D) x 2,300 (H) mm	± 5mm		
Weight	Approx. 668kg	± 5%		
IP Grade	20	-		
<b>Communication</b>				
Communication Interface	Ethernet/RS-485	Modbus TCP/ Modbus RTU		
Monitoring	RS-232C	-		
<b>Operating Conditions</b>				
Operating Temperature <sup>3</sup>	Charging	0 ~ 10°C	<0.2P	
		10 ~ 35°C	<2P	
		35 ~ 45°C	<1P	
	Discharging	0 ~ 55°C	-	
<b>Environment</b>				
Ambient Temperature	23±5°C	-		
Storage Humidity	<60±25% RH	Non-condensing		
Storage Temperature <sup>4</sup>	1 Year	-20 ~ 25°C	30≤ SOC ≤50%	
	6 Months	-20 ~ 35°C		
	3 Months	-20 ~ 45°C		
	<1 Week	-20 ~ 60°C		
<b>Expected Cycle &amp; Calendar Life<sup>5</sup></b>				
Cycle Life @ DoD 90%	≥6,000 cycles	@ 25±3°C, 1C/1C, SOH 70%		
Cycle Life @ DoD 80%	≥8,000 cycles	@ 25±3°C, 1C/1C, SOH 70%		
Calendar Life	Up to 15 years	@ 25±3°C, SOC ≤80%, SOH 70%		
<b>Certification &amp; Compliance</b>				
Certifications <sup>6</sup>	UL 1642, UL 1973, IEC 62619, UL 9540A, UN 38.3	Cell level		
	CE, IEC 62619, UN 38.3	Module level		
	CE, IEC 62619, IEC 60730-1 Annex H	Rack level		
Compliance	RoHS II, REACH	-		

\*P : Power-rate / C : Current-rate

- The usable energy may change depending on the calendar life of the battery cells.
- After max. charging or discharging, it is recommended to rest the battery rack until the cell temperature returns to 23±5°C.
- Operating temperature is based on the cell temperature.
- When resting the battery system after an operation for longer than 1 month, the user shall ensure that the SOC is above 30%. The ambient temperature shall be controlled at 23±5°C when resting the battery system. During storage, the temperature and SOC conditions shall always be adhered to.
- Cycle and calendar life shall be depending on the load profile, and the warranty condition may differ according to Kokam Limited Product Warranty.
- Certification update (incl. model name). Expected to be completed in 1Q 2022.

#### DISCLAIMERS OF WARRANTIES:

All materials and services on this document are provided "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of merchantability or fitness for a particular purpose, or the warranty of non-infringement. This document could include technical or other mistakes, inaccuracies or typographical errors. Kokam assumes no responsibility for errors or omissions in the information, documents, software, materials and/or services which are referenced by or linked to this document. Kokam does not grant any express or implied right to any person or business entity under any patents, copyrights, trademarks, or trade secret information with respect to the materials and services. No portion of the information or documents may be reproduced in any form or by any means without the prior written consent of kokam. In no event shall kokam be liable to any person or business entity for any special, punitive, incidental, indirect or consequential damages based on any use of this document.